



Bemidji 218-759-8518

Brainerd 218-833-1000

Duluth 218-249-1288

Initial Treatment for Jacuzzi @ Ease System

(Use these steps when spa water is drained and refilled)

- Add half a bottle of METAL CONTROL
- Add 4 Oz. of 4-1 CLARIFIER or UNIQUE
- Add the FROG JUMP START packet or 3 oz Dichlor Granules
- Turn Blue mineral cartridge to 7 (Fully open)
- Turn the Grey SmartChlor Cartridge to the setting of 5 (250-450 gallon spas). Place the cartridges in the filter attachment and place put in the right side (Standing over the filters)

Confirm the top Single Color Match indicator tab on your frog ease test strip is reading

SmartChlor in the water

- Wait until spa is at its set temperature.
- Pull Out & Rinse Filters after 24-36 hours
- Check and adjust the pH to read between 7.2 and 7.8 using FROG TEST STRIP



Regular Maintenance

- Test water with FROG EASE TEST STRIP and adjust pH weekly
- When the grey SmartChlor is empty, usually 3-4 weeks, replace the cartridge with a new cartridge making sure to adjust the setting to 5
- A 2 oz. bag of FROG MAINTAIN SHOCK or 1 cap of OXY PLUS.
(Add this **everytime** the grey SmartChlor cartridge is replaced)
- The blue mineral cartridge on top lasts approximately 4 months.
- Rinse filters weekly
- Add 2 Oz. 4-1 CLARIFIER or UNIQUE weekly in hard water conditions.
- If foaming occurs use SCUMBALL and/or FOAM OUT

